

Micronas.5963
09/743,926

8.(Previously Amended) An integrated circuit sensor, comprising:

a comparator that receives an input signal, and compares said input signal against a plurality of predetermined threshold values and provides a plurality of comparator output signals each indicative of whether or not said input signal exceeds an associated one of said plurality of predetermined threshold values; and

an output stage that receives said plurality of comparator output signals and encodes state information associated with said plurality of comparator output signals to provide on a integrated circuit lead an encoded output signal indicative of said state information associated with said plurality of comparator signals,

wherein said output stage comprises means for generating said encoded output signal using pulse width modulation, wherein said state information is encoded within said encoded output signal based upon the pulse/pause ratio of said encoded output signal.

OK
to
enter
JES
10/6/04

9.(Cancelled)

10.(Cancelled)

11.(Cancelled)

BEST AVAILABLE COPY

Micronas.5963
09/743,926

12.(Previously Amended) An integrated circuit sensor, comprising:

a magnetic field transducer comprising a Hall effect transducer that generates and provides an input signal;

a comparator that receives said input signal, and compares said input signal against a plurality of predetermined threshold values and provides a plurality of comparator output signals each indicative of whether or not said input signal exceeds an associated one of said plurality of predetermined threshold values;

an output stage that receives said plurality of comparator output signals and encodes state information associated with said plurality of comparator output signals to provide on a integrated circuit lead an encoded output signal indicative of said state information associated with said plurality of comparator signals; and

a control unit that includes a memory device that stores and provides said plurality of predetermined threshold values.

13.(Previously Amended) The integrated circuit sensor of claim 12, wherein said memory device comprises a read/write memory device that allows said plurality of predetermined threshold values to be changed and stored in said read/write memory device.

14.(Previously Amended) The integrated circuit sensor of claim 12, comprising

means for reading updated predetermined threshold values that are input to said integrated circuit sensor through said integrated circuit lead that also receives said encoded output signal, and for storing said updated predetermined threshold values in said memory device, which provides said updated predetermined threshold values to said comparator for comparison against said input signal.

Micronas.5963
09/743,926

15.(Cancelled)

16.(Cancelled)

17.(Previously Amended) An integrated circuit sensor, comprising:

a transducer element that provides a transducer output signal;

a comparator that receives said transducer output signal, and compares a signal indicative of said transducer output signal against a plurality of adjustable threshold values and provides a plurality of comparator output signals each indicative of one of an associated plurality of switching states; and

an output stage that receives said plurality of comparator output signals and encodes switching state information associated with said plurality of comparator output signals to provide on a bi-directional integrated circuit lead an encoded output signal indicative of said state information associated with said plurality of comparator signals;

wherein said output stage comprises means for generating said encoded output signal using pulse width modulation, wherein said state information is encoded within said encoded output signal based upon the pulse/pause ratio of said encoded output signal.

18.(Cancelled)

19.(Previously Amended) The integrated circuit sensor of claim 17, wherein said comparator comprises hysteresis on each of said predetermined threshold values.

Micronas.5963
09/743,926

20.(Cancelled)

21.(Cancelled)

22.(Cancelled)

23.(Currently Amended) An integrated circuit sensor, comprising:

- a transducer element that provides a transducer output signal;
- an amplifier that receives said transducer output signal and provides an amplified transducer output signal;
- a comparator network that receives said amplified transducer output signal, and compares a signal indicative of said amplified transducer output signal against a plurality of adjustable threshold values to determine a state of said amplified transducer output signal, and provides a plurality of comparator output signals indicative of said state of said amplified transducer output signal; and
- an output stage that receives said plurality of comparator output signals and encodes switching state information associated with said plurality of comparator output signals to provide on a integrated circuit lead an encoded output signal indicative of said state; and
- a control unit that includes a memory device that stores and provides said plurality of adjustable threshold values.

Micronas.5963
09/743,926

24.(Currently Amended) An integrated circuit sensor, comprising:

a transducer element that comprises a magnetic field transducer and provides a transducer output signal;

an amplifier that receives said transducer output signal and provides an amplified transducer output signal;

a comparator network that receives said amplified transducer output signal, and compares a signal indicative of said amplified transducer output signal against a plurality of adjustable threshold values to determine a state of said amplified transducer output signal, and provides a plurality of comparator output signals indicative of said state of said amplified transducer output signal; and

an output stage that receives said plurality of comparator output signals and encodes switching state information associated with said plurality of comparator output signals to provide on a integrated circuit lead an encoded output signal indicative of said state; and

a control unit that includes a memory device that stores and provides said plurality of adjustable threshold values.

25.(Currently Amended) An integrated circuit sensor, comprising:

a magnetic field transducer that generates and provides an said input signal;

a comparator that receives said input signal, and compares said input signal against a plurality of predetermined threshold values and provides a plurality of comparator output signals each indicative of whether or not said input signal exceeds an associated one of said plurality of predetermined threshold values;

an output stage that receives said plurality of comparator output signals and encodes state information associated with said plurality of comparator output signals to provide on a integrated

Micronas.5963
09/743,926

circuit lead an encoded output signal indicative of said state information associated with said plurality of comparator signals; and

a control unit that includes a memory device that stores and provides said plurality of predetermined threshold values.

26.(Previously Amended) An integrated circuit sensor, comprising:

a transducer element comprising a magnetic field transducer that provides a transducer output signal;

a comparator that receives said transducer output signal, and compares a signal indicative of said transducer output signal against a plurality of adjustable threshold values and provides a plurality of comparator output signals each indicative of one of an associated plurality of switching states;

an output stage that receives said plurality of comparator output signals and encodes switching state information associated with said plurality of comparator output signals to provide on a bi-directional integrated circuit lead an encoded output signal indicative of said state information associated with said plurality of comparator signals; and

a control unit that includes a memory device that stores and provides said plurality of predetermined threshold values.

27.(Previously Added) The integrated circuit sensor of claim 26, wherein said memory device comprises a read/write memory device that allows said plurality of predetermined threshold values to be changed and stored in said read/write memory device.

Micronas.5963
09/743,926

28.(Currently Amended) The integrated circuit sensor of claim 26, comprising
means for reading updated predetermined threshold values that are input to said integrated
circuit sensor through said integrated circuit lead that also receives said encoded output signal, and
for storing said updated predetermined threshold values in said memory device, which provides said
updated predetermined threshold values to said comparator for comparison against said signal
indicative of said transducer output signal~~input signal~~.

29.(Cancelled)

30.(Previously Amended) An integrated circuit sensor, comprising:
a transducer element that comprises a magnetic field transducer and provides a transducer
output signal;
an amplifier that receives said transducer output signal and provides an amplified transducer
output signal;
a comparator network that receives said amplified transducer output signal, and compares a
signal indicative of said amplified transducer output signal against a plurality of adjustable threshold
values to determine a state of said amplified transducer output signal, and provides a plurality of
comparator output signals indicative of said state of said amplified transducer output signal;
an output stage that receives said plurality of comparator output signals and encodes
switching state information associated with said plurality of comparator output signals to provide on
a integrated circuit lead an encoded output signal indicative of said state; and
a control unit that includes a memory device that stores and provides said plurality of
predetermined threshold values.

Micropas.5963
09/743,926

31.(Previously Added) The integrated circuit sensor of claim 30, wherein said memory device comprises a read/write memory device that allows said plurality of predetermined threshold values to be changed and stored in said read/write memory device.

32.(Currently Amended) The integrated circuit sensor of claim 30, comprising means for reading updated predetermined threshold values that are input to said integrated circuit sensor through said integrated circuit lead that also receives said encoded output signal, and for storing said updated predetermined threshold values in said memory device, which provides said updated predetermined threshold values to said comparator for comparison against said signal indicative of said amplified transducer output signal~~input signal~~.

33.(Cancelled)

34.(Previously Amended) The integrated circuit sensor of claim 8, comprising a control unit that includes a memory device that stores and provides said plurality of predetermined threshold values.

35.(Previously Added) The integrated circuit sensor of claim 34, wherein said memory device comprises a read/write memory device that allows said plurality of predetermined threshold values to be changed and stored in said read/write memory device.

Micronas.5963
09/743,926

36.(Previously Added) The integrated circuit sensor of claim 34, comprising
means for reading updated predetermined threshold values that are input to said integrated
circuit sensor through said integrated circuit lead that also receives said encoded output signal, and
for storing said updated predetermined threshold values in said memory device, which provides said
updated predetermined threshold values to said comparator for comparison against said input signal.

37.(Cancelled)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☒ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.